

PIRANHA SEWER CLEANING HOSE

Piranha Hose is constructed from materials selected to provide rugged and reliable service under even the most severe and demanding conditions found in high pressure sewer cleaning applications. Every Piranha sewer cleaning hose is constructed with a poly-olefin tube which provides maximum resistance to the hydrolysis commonly associated with other thermoplastic tube materials. Reinforcement with high tensile polyester fibre contributes to an exceptionally low volumetric expansion rate and eliminates loss of strength from moisture absorption. A polyether-urethane cover provides exceptional cut, abrasion and fungus resistance. And lastly, all components are bonded together to maximise fitting retention and wear resistance, and provide smaller minimum bend radii.



SP HOSE

Hose#	Hose Colour	Hose ID mm(in)	Hose OD mm(in)	Max. Operating Pressure Bar(psi)	Min. Burst Pressure Bar(psi)	Min. Bend Radius	Cover Thickness	Weight per/m
SP-12	Orange	19(3/4")	30(1-3/16")	172(2500)	430(6250)	125mm	1.77mm	416g/m
SP-16	Orange	25(1")	37(1-7/16")	172(2500)	430(6250)	150mm	1.65mm	595g/m
SP-20	Orange	32(1-1/4")	46(1-13/16")	172(2500)	430(6250)	200mm	2.41mm	877g/m

1/2" HOSE SERIES



Hose#	Hose Colour	Hose ID mm(in)	Hose OD mm(in)	Max. Operating Pressure Bar(psi)	Min. Burst Pressure Bar(psi)	Min. Bend Radius	Weight per/m
LL8-3000	Blue	12.8(1/2")	21.2(7/8")	207(3000)	517(7500)	100mm	229g/m
LL8-4000	Green	12.8(1/2")	21.2(7/8")	275(4000)	690(10000)	100mm	232g/m
SHP-8	Black	12.8(1/2")	21.2(7/8")	275(4000)	827(12000)	75mm	282g/m
SHBK-10	Black	15.9(5/8")	23.0(0.91")	275(4000)	827(12000)	100mm	232g/m
LL8-5000	Green	12.8(1/2")	21.2(7/8")	275(4000)	827(12000)	75mm	282g/m

LATERAL LINE HOSE



Hose#	Hose Colour	Hose ID mm(in)	Hose OD mm(in)	Max. Operating Pressure Bar(psi)	Min. Burst Pressure Bar(psi)	Min. Bend Radius	Weight per/m
LL3-5000	Red	4.8(3/16")	10.5(7/16")	275(4000)	850(12500)	45mm	47g/m
LL4-5000	Red	6.4(1/4")	12.6(1/2")	275(4000)	850(12500)	65mm	74g/m
LL6-5000	Red	9.7(3/8")	16.4(5/8")	275(4000)	850(12500)	75mm	166g/m

PORTABLE HAND SWAGER

Easy to use and portable. Swages both menders and male end fittings. Its tapered die blocks make dies easy to remove.



HYDRAULIC SWAGER

- No electrical power required
- Designed for field operation
- Can be used to apply end fittings as well as menders



HOSE SWAGING FITTINGS



Hose fittings for 1/4", 3/8", 1/2", 3/4" & 1" Sewer Hose. Male, female and joiners available.