

## Big Mouth Flow-Through

Part Number	Nominal Size	Bypass Diameter (NPT)	Range of Use	Maximum Back Pressure		Inflation Pressure	Product Weight	Deflated Length	Deflated Diameter	Inflation Thread	Chain / Eye bolts
369068	<b>6"</b> (150 mm)	4" M	5.69"-6.34" (145-161 mm)	11 psi (0,76 bar)	25 ft. (7.6 M)	30 psi (2,1 bar)	7 lbs (3.2 kg)	13.25" (337 mm)	5.38" (137 mm)	1/4" (1)	3/8" (1)
374068	<b>6" - 10"</b> (150-250 mm)	4" M	5.75"-10.25" (146-260 mm)	10 psi (0,69 bar)	23 ft. (10 M)	40 psi (2,8 bar)	15 lbs (6.8 kg)	24.5" (622 mm)	5.65" (146 mm)	1/4" (1)	3/8" (1)
369088	<b>8"</b> (200 mm)	6" M	7.75"-8.45" (195-215 mm)	11 psi (0,76 bar)	25 ft. (7.6 M)	30 psi (2,1 bar)	10 lbs (4.5 kg)	16" (406 mm)	7.5" (191 mm)	1/4" (1)	3/8" (1)
269008	<b>8" - 10"</b> (200-300 mm)	4" M	7.25"-10.25" (185-250 mm)	11 psi (0,76 bar)	25 ft. (7.6 M)	35 psi (2,4 bar)	8.8 lbs (4 kg)	14.88" (378 mm)	6.94" (176 mm)	1/4" (1)	3/8" (1)
374088	<b>8" - 12"</b> (200-300 mm)	4" M	7"-12.25" (178-311 mm)	15 psi (1 bar)	34 ft. (10.5 M)	35 psi (2,4 bar)	22 lbs (10 kg)	26" (660 mm)	6.75" (165 mm)	1/4" (1)	3/8" (1)
376088	<b>8" - 12"</b> (200-300 mm)	6" M	7"-12.25" (178-311 mm)	15 psi (1 bar)	34 ft. (10.5 M)	35 psi (2,4 bar)	22 lbs (10 kg)	26" (660 mm)	6.76" (165 mm)	1/4" (1)	3/8" (1)
369108	<b>10"</b> (250 mm)	8" OD*	9.75"-10.46" (250-266 mm)	11 psi (0,76 bar)	25 ft. (7.6 M)	30 psi (2,1 bar)	17 lbs (7.7 kg)	20" (508 mm)	9.13" (232 mm)	1/4" (1)	3/8" (1)
269018	<b>10" - 12"</b> (250-300 mm)	6" M	9.25"-12.25" (235-311 mm)	11 psi (0,76 bar)	25 ft. (7.6 M)	30 psi (2,1 bar)	15.7 lbs (7.12 kg)	17.25" (438 mm)	8.81" (224 mm)	1/4" (1)	3/8" (1)
369128	<b>12"</b> (300 mm)	10" OD*	11.75"-12.52" (300-318 mm)	11 psi (0,76 bar)	25 ft. (7.6 M)	30 psi (2,1 bar)	21 lbs (9.5 kg)	20" (508 mm)	11.13" (283 mm)	1/4" (1)	3/8" (1)
269028	<b>12" - 15"</b> (300-380 mm)	6" M	10.62"-15.25" (270-387 mm)	11 psi (0,76 bar)	25 ft. (7.6 M)	30 psi (2,1 bar)	20 lbs (9 kg)	17.88" (454 mm)	10.25" (260 mm)	1/4" (1)	3/8" (1)
376128	<b>12" - 18"</b> (300-450 mm)	6" M	11.25"-18.25" (286-464 mm)	10 psi (0,69 bar)	23 ft. (10 M)	25 psi (1,7 bar)	45 lbs (21 kg)	28" (711 mm)	11" (279 mm)	1/4" (1)	3/8" (1)
378128	<b>12" - 18"</b> (300-450 mm)	8" M	11.25"-18.25" (286-464 mm)	10 psi (0,69 bar)	23 ft. (10 M)	25 psi (1,7 bar)	45 lbs (21 kg)	28" (711 mm)	11" (279 mm)	1/4" (1)	3/8" (1)
369158	<b>15"</b> (380 mm)	12" OD*	13.9"-15.56" (353-395 mm)	11 psi (0,76 bar)	25 ft. (7.6 M)	30 psi (2,1 bar)	26 lbs (11.8 kg)	20" (508 mm)	13.13" (333 mm)	1/4" (1)	3/8" (1)
369188	<b>18"</b> (450 mm)	15" OD*	16.88"-18.74" (429-476 mm)	11 psi (0,76 bar)	25 ft. (7.6 M)	30 psi (2,1 bar)	31 lbs (14 kg)	20" (508 mm)	16.13" (410 mm)	1/4" (1)	3/8" (1)
369218	<b>21"</b> (525 mm)	18" OD*	20.01"-21.81" (508-554 mm)	11 psi (0,76 bar)	25 ft. (7.6 M)	30 psi (2,1 bar)	37 lbs (16.8 kg)	20" (508 mm)	19.13" (486 mm)	1/4" (1)	3/8" (1)
369248	<b>24"</b> (600 mm)	20" OD*	22.63"-24.98" (575-634 mm)	11 psi (0,76 bar)	25 ft. (7.6 M)	30 psi (2,1 bar)	42 lbs (19 kg)	20" (508 mm)	21.13" (537 mm)	1/4" (1)	3/8" (1)

Part Number	Nominal Size	Bypass Diameter (NPT)	Range of Use	Maximum Back Pressure		Inflation Pressure	Product Weight	Deflated Length	Deflated Diameter	Inflation Thread	Chain / Eye bolts
<b>Multi-Size Big Mouth Plugs</b>											
376148	<b>14" - 21"</b> (375-525 mm)	6" M	13.6"-21.25" (345-540 mm)	10 psi (0,69 bar)	23 ft. (10 M)	25 psi (1,7 bar)	60 lbs (27 kg)	30" (762 mm)	13.25" (337 mm)	1/8" (1)	3/8" (2)
378148	<b>14" - 21"</b> (375-525 mm)	8" M	13.6"-21.26" (345-540 mm)	10 psi (0,69 bar)	23 ft. (10 M)	25 psi (1,7 bar)	60 lbs (27 kg)	30" (762 mm)	13.25" (337 mm)	1/8" (1)	3/8" (2)
380148	<b>14" - 21"</b> (375-525 mm)	10" M	13.6"-21.27" (345-540 mm)	10 psi (0,69 bar)	23 ft. (10 M)	25 psi (1,7 bar)	60 lbs (27 kg)	30" (762 mm)	13.25" (337 mm)	1/8" (1)	3/8" (2)
376188	<b>18" - 24"</b> (450-600 mm)	6" M	16.5"-24.25" (419-616 mm)	10 psi (0,69 bar)	23 ft. (10 M)	22 psi (1,5 bar)	90 lbs (41 kg)	34" (864 mm)	16" (406 mm)	1/8" (1)	1/2" (2)
378188	<b>18" - 24"</b> (450-600 mm)	8" M	16.5"-24.26" (419-616 mm)	10 psi (0,69 bar)	23 ft. (10 M)	22 psi (1,5 bar)	90 lbs (41 kg)	34" (864 mm)	16" (406 mm)	1/8" (1)	1/2" (2)
380188	<b>18" - 24"</b> (450-600 mm)	10" M	16.5"-24.27" (419-616 mm)	10 psi (0,69 bar)	23 ft. (10 M)	22 psi (1,5 bar)	90 lbs (41 kg)	34" (864 mm)	16" (406 mm)	1/8" (1)	1/2" (2)

OD – Outside Diameter Straight Tube

Always block plugs when conducting air tests.

Pneumatic Plugs



VISIT US ONLINE [seca.com.au](http://seca.com.au)