

Muni-Ball

Part Number	Nominal Size	Bypass Diameter (NPT)	Range of Use	Maximum Back Pressure	Inflation Pressure	Product Weight	Deflated Length	Deflated Diameter	Inflation Thread	Chain / Eye bolts	
262008	1.5" (40 mm)	1/8" M	1.49"-1.88" (38-48 mm)	22 psi (1,5 bar)	50 ft (15 M)	40 psi (2,8 bar)	0.3 lbs (0.2 kg)	3.8" (97 mm)	1.4" (36 mm)	Molded in Valve	Removable Chain
262010	2" (50 mm)	1/8" F	1.88"-2.25" (48-57 mm)	22 psi (1,5 bar)	50 ft (15 M)	40 psi (2,8 bar)	0.4 lbs (0.3 kg)	6" (152 mm)	1.75" (44 mm)	Molded in Valve	Removable Chain
262021	3" (75 mm)	3/4" F	2.62"-3.25" (67-83 mm)	22 psi (1,5 bar)	50 ft (15 M)	40 psi (2,8 bar)	1.25 lbs (0.5 kg)	8" (203 mm)	2.5" (64 mm)	Molded in Valve	Removable Chain
262048	4" (100 mm)	3/4" F	3.25"-4.25" (83-108 mm)	22 psi (1,5 bar)	50 ft (15 M)	40 psi (2,8 bar)	1.5 lbs (0.7 kg)	8" (203 mm)	3.13" (80 mm)	Molded in Valve	1/4" (1)
265048	4" - 6" (100-150 mm)	3/4" F	3.75"-6.25" (100-150 mm)	17 psi (1,2 bar)	40 ft (12 M)	35 psi (2,4 bar)	2.5 lbs (1.1 kg)	10.75" (273 mm)	3.46" (88 mm)	1/8"	1/4" (1)
#311088	4" - 8" (100-200 mm)	†3/4" NPT	3.75"-8.25" (100-210mm)	15 psi (1 bar)	34 ft. (10.5 M)	45 psi (3 bar)	4.6 lbs (2.1 kg)	23" (585mm)			Attachment Point
262064	6" (150 mm)	1 1/2" F	4.50"-6.25" (144-159 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	35 psi (2,4 bar)	2 lbs (1 kg)	7" (178 mm)	4.5" (112 mm)	1/8"	1/4" (1)
265068	6" - 8" (150-200 mm)	1 1/2" F	5.50"-8.35" (133-212 mm)	17 psi (1,2 bar)	40 ft (12 M)	35 psi (2,4 bar)	6 lbs (2.7 kg)	13" (330 mm)	5" (125 mm)	1/4"	3/8" (1)
#311128	6" - 12" (150-300 mm)	†1" NPT	5.50"-12.4" (140-317 mm)	15 psi (1 bar)	34 ft. (10.5 M)	45 psi (3 bar)	89.4 lbs (4.3kg)	25" (635 mm)			Attachment Point
262080	8" (200 mm)	3" F	7.00"-8.25" (178-210 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	35 psi (2,4 bar)	5 lbs (2.3 kg)	10" (254 mm)	6.75" (170 mm)	1/4"	3/8" (1)
265078	8" - 10" (200-250 mm)	2" F	7.00"-10.25" (178-260 mm)	17 psi (1,2 bar)	40 ft (12 M)	30 psi (2,1 bar)	9 lbs (3 kg)	14.5" (368 mm)	6.75" (171 mm)	1/4"	3/8" (1)
#212128	8" - 12" (200-300 mm)	2" NPT	5.50"-12.24" (140-317 mm)	15 psi (3 bar)	34 ft (10.5 M)	45 psi (3 bar)	12.10 lbs (5.5kg)	18.5" (470mm)			Attachment Point
#312168	8" - 16" (200-400 mm)	†2" NPT	7.5"-16.2" (191-412 mm)	15 psi (1 bar)	34 ft. (10.5 M)	45 psi (3 bar)	15.8 lbs (7.2kg)	28" (710 mm)			Attachment Point
262110	10" (250 mm)	3" F	9.00"-10.25" (229-260 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	35 psi (2,4 bar)	9 lbs (4 kg)	11.75" (298 mm)	8.75" (222 mm)	1/4"	3/8" (1)
262129	12" (300 mm)	3" F	10.50"-12.25" (267-311 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	35 psi (2,4 bar)	13 lbs (6 kg)	13.75" (350 mm)	10.25" (260 mm)	1/4"	3/8" (1)
265128	12" - 18" (300-450 mm)	4" F	10.75"-18.75" (273-477 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	25 psi (1,7 bar)	32 lbs (14.5 kg)	27.25" (692 mm)	10.5" (267 mm)	1/4"(2)	3/8" (2)
#214188	12" - 17.7" (300-450 mm)	3" BSP	10.75"-18.75" (273-476 mm)	15 psi (1bar)	34ft. (10.5 M)	45 psi (3 bar)	28 lbs (12.7kg)	25" (635mm)			Attachment Point
262137	15" - 16" (375-400 mm)	3" F	14.0"-16.0" (356-413 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	35 psi (2,4 bar)	33 lbs (15 kg)	19.75" (502 mm)	13.75" (346 mm)	1/4"	3/8" (1)
*412308	15" - 30" (375-750 mm)	†2 1/2" M	14.5"-30.5" (368-775 mm)	**11 psi (0,76 bar)	25 ft. (7.6 M)	25 psi (1,7 bar)	62 lbs (28 kg)	51" (1289 mm)	14" (356 mm)	1/4" & 1/2"	3/8" (4)
*414308	15" - 30" (375-750 mm)	†4" M	14.5"-30.5" (368-775 mm)	**11 psi (0,76 bar)	25 ft. (7.6 M)	25 psi (1,7 bar)	105 lbs (48 kg)	51" (1289 mm)	14" (356 mm)	1/4" & 1/2"	3/8" (4)
262188	18" (450 mm)	4" F	17.5"-19.5" (445-504 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	25 psi (1,7 bar)	79 lbs (36 kg)	24.75" (629 mm)	16.9" (429 mm)	1/4"	1/2" (2)
*312408	20" - 40" (500-1000 mm)	†2" M	19"-40" (475-1000mm)	8.7 psi (0,6 bar)	20 ft. (6.1 M)	22 psi (1,5 bar)	88 lbs (40 kg)	46.25" (1175 mm)	18.5" (470 mm)	1/4" & 1/2"	1/2" (2)
*314408	20" - 40" (500-1000mm)	†4" M	19"-40" (475-1000mm)	8.7 psi (0,6 bar)	20 ft. (6.1 M)	22 psi (1,5 bar)	95 lbs (43 kg)	46.25" (1175 mm)	18.5" (470 mm)	1/4" & 1/2"	1/2" (2)
*316408	20" - 40" (500-1000mm)	†6" M	19"-40" (475-1000mm)	8.7 psi (0,6 bar)	20 ft. (6.1 M)	22 psi (1,5 bar)	106 lbs (48 kg)	46.25" (1175 mm)	18.5" (470 mm)	1/4" & 1/2"	1/2" (2)
262218	21" (525 mm)	4" F	18.55"-21.38" (479-543 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	25 psi (1,7 bar)	87 lbs (39 kg)	26" (660 mm)	18.25" (462 mm)	1/4"	1/2" (2)
262242	24" (600 mm)	†4" F	22.0"-25" (558-632 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	25 psi (1,7 bar)	124 lbs (56 kg)	28.75" (730 mm)	21.25" (538 mm)	1/4"	1/2" (2)
*410428	24" - 42" (600-1050 mm)	†4" M	22.5"-42.5" (600-1050 mm)	**9 psi (0,62 bar)	20 ft. (6.1 M)	25 psi (1,7 bar)	150 lbs (68 kg)	52" (1320 mm)	22" (560 mm)	1/4" & 1/2"	1/2" (4)
*314488	24" - 48" (600-1200 mm)	†4" M	20"-50" (510-1270 mm)	**10 psi (0,7 bar)	23 ft. (7 M)	22 psi (1,5 bar)	150 lbs (68 kg)	68" (1730 mm)	20" (485 mm)	1/2"	5/8" (3)
*316488	24" - 48" (600-1200 mm)	†6" M	20"-50" (510-1270 mm)	**10 psi (0,7 bar)	23 ft. (7 M)	22 psi (1,5 bar)	153 lbs (69.5 kg)	68" (1730 mm)	20" (485 mm)	1/2"	5/8" (3)
*314608	30" - 60" (700-1500 mm)	†4" M	26.5"-60.5" (700-1537 mm)	**10 psi (0,7 bar)	23 ft. (7 M)	22 psi (1,5 bar)	210 lbs (95.4 kg)	102" (2590 mm)	26" (661 mm)	1/2" (2)	5/8" (3)
*414608	40" - 60" (1000-1500 mm)	†4" M	38"-60" (965-1537 mm)	**8.7 psi (0,62 bar)	20 ft. (6.1 M)	25 psi (1,7 bar)	350 lbs (159 kg)	73" (1855 mm)	37.25" (946 mm)	1/4" & 1/2"	1/2" (4)
*314728	48" - 72" (1200-1800 mm)	†4" M	44"-72.25" (1118-1835 mm)	6 psi (0,41 bar)	14 ft. (4.3 M)	12 psi (0,83 bar)	310 lbs (141 kg)	100" (2540 mm)	43" (1092 mm)	1/2" (2)	5/8" (3)
*314968	54" - 96" (1400-2400 mm)	†4" M	54"-96.25" (1400-2450 mm)	6 psi (0,41 bar)	14 ft. (4.3 M)	11 psi (0,75 bar)	500 lbs (228 kg)	128" (3200 mm)	50" (1270 mm)	1/2" (2)	5/8" (3)
#312248	11.8" - 23.6" (300-600mm)	3"BSP	11" - 24.2" (280-615mm)	15 psi (1 bar)	34ft. (10.5 M)	45 psi (3 bar)	35 lbs (15.9 kg)	37" (940 mm)			Attachment Point

*Rupture Disc | †Flexible Bypass | #I-Series Plug

**See chart on page 10 for backpressure ratings by diameter

