

ROTOPULS VIBRATION NOZZLES: Working pressure up to 280 bar

Part #	Thread	Rotating Nozzles	Thrust Nozzles	Front Jet	Measures	Weight	Applicability from dia.	min. l/min at 100 bar
02.100AE	1"	4x M10	3x M10	on request	Ø100x180mm	7.4kg	200-600mm	200
02.100BE	1 1/4"	4x M10	3x M10	on request	Ø100x180mm	7.4kg	200-600mm	200
01.028AE	1/4"	2x M4	3x M6	on request	Ø28x62mm	200g	30-100mm	10
04.040AE	1/2"	4x M4	3x M6	on request	Ø40x85mm	520g	70-150mm	20
04.050AE	1/2"	4x M6	3x M6	on request	Ø50x100mm	1.1kg	70-200mm	70
04.050BE	3/4"	4x M6	3x M6	on request	Ø50x100mm	1.1kg	70-200mm	70
04.060EK	1"	4x M6	3x M8	on request	Ø60x118mm	1.6kg	100-300mm	100
04.060E	1"	4x M6	3x M8	on request	Ø60x170mm	2.6kg	100-300mm	100
04.100AE	1"	4x M10	3x M10		Ø100x180mm	7.4kg	200-600mm	200
04.100BE	1 1/4"	4x M10	3x M10		Ø100x180mm	7.4kg	200-600mm	200
Bulldog® Rotopuls for recycling water								
400.100AE	1"	5x M10	6x M10		Ø130x320mm	11kg	200-1000mm	100
400.100BE	5/4"	5x M10	6x M10		Ø130x320mm	11kg	200-1000mm	100